

Quotation Request //

US Government Printing Office

Agency Publishing Services
732 North Capitol Street, NW
Washington DC 20401-0001

JACKET:327-372

Issue Date and Time: 09/25/2006 5:47 PM

Quotations are Due By:

(Eastern Time)10:00 AM on 09/26/2006

Submit Fax Quotes to: 00000000

TITLE: Information Operations (IO) and 1st IO Command (Land) - Trifold

QUANTITY: 1050 DOLLARS worth

FIXED PRICE-INDEFINITE QUANTITY CONTRACT:

AWARD WILL BE BASED ON THE LARGEST QUANTITY OF FORMS FOR A TOTAL OF \$1,050.00. POTENTIAL VENDORS MUST SUBMIT A QUANTITY, NOT A PRICE. IN THE EVENT OF A TIE QUANTITY, THE AWARD WILL BE DETERMINED BY THE OVERALL LOWEST DISCOUNTED COST. ADDITIONALLY, A COST MUST BE SUBMITTED FOR EACH ADDITIONAL 100 COPIES.

TRIM SIZE: Flat: 11 x 8-1/2"; Folded: 3-2/3 x 8-1/2"

PAGES: Face and back

SCHEDULE:

Furnished Material will be available for pickup by 09/26/2006

Deliver complete (to arrive at destination) by 10/02/2006

F.O.B. destination

NOTE: No deliveries accepted after 3:00 P.M.

QUALITY LEVEL: 2 Quality Assurance Through Attributes (GPO PUB 310.1, effective May 1979 (Rev. 8-02)) applies.

DESCRIPTION:

RESTRICTION ON LOCATION OF PRODUCTION FACILITIES: All production facilities used in the manufacture of the product(s) ordered under this contract must be located within a 50-mile radius of Fort Belvoir, VA 22060.

PRINTING/COATING: Six panel form prints full coverage, on both sides, with black line matter plus 4-color process illustrations, images built from process colors plus line matter reversing out to appear white. After printing, coat the entire surface of both sides with a clear, non-yellowing gloss varnish.

PRESS SHEET INSPECTION: Call (202) 512-1162, between the hours of 8:00 a.m. and 2:00 p.m., prevailing eastern time, with 2 workdays notice.

NOTE: PSI MUST BE HELD IMMEDIATELY FOLLOWING IN-PLANT PROOF INSPECTION.

Press sheets will be inspected at the contractor's plant for quality conformance. Note: A press sheet inspection is for the purpose of setting specific standards that are to be maintained throughout the entire run. It does not constitute a prior approval of the entire run.

Press sheets must contain one color bar for each color placed parallel to the proofer's ink rollers. The control bars must show areas consisting of 3/16 x 3/16" minimum solid color patches; tint patches of 25, 50, 75%; dot gain scale (GATF, BRUNNER, or GRETAG); and gray balance patches for process color, repeated across the entire press sheet. The density must be constant across the full width of the sheet with deviations not to exceed plus or minus 5%. For viewing of the press sheets, the contractor must provide a densitometer and controlled lighting using overhead viewing lights with 5000 degree Kelvin lumination.

NOTE: Must be printed on a press capable of printing four colors in a single pass through the press (minimum four printing units).

MATERIAL FURNISHED: Contractor to pickup at GPO. .

One CD-R generated on an IBM compatible using InDesign CS2, Illustrator CS2, Photoshop CS2 in native format and Adobe PDF software.

Prior to image processing, the contractor shall perform a basic check (preflight) of the furnished media and publishing files to assure correct output of the required reproduction image. Any errors, media damage, or data corruption that might interfere with proper file image processing must be reported to the contract administrator.

The contractor shall create or change any necessary trapping, set proper screen angles and screen frequency, and define file output selection for the imaging device being utilized. Furnished files must be imaged as necessary to meet the assigned quality level.

PAPER: * Must be in accordance with JCP Paper Specification Standards in effect on date of this order
JCP Code* L12, White No. 2 Coated Cover, Gloss-Finish, basis weight 100 lbs. per 500 sheets, basis size 20x26".

COLOR OF INK:

4-Color Process plus gloss varnish.

PRINT PAGE: Head to Head

MARGINS:

Face/Back: Bleeds all sides (uncommon). Follow furnished electronic media.

PROOFS:

One set of digital one-piece composite laminated color proofs of form on the actual production stock (Kodak Approval, Screen TrueRite, Dupont Thermal Waterproof, Polaroid PolaProof, CreoSpectrum, or Fuji Final Proof) with a minimum resolution of 2400 dpi. At contractor's option, a film-based composite laminated color proof on the actual production stock may be submitted provided direct to plate is used to produce the final product. The make and model number of the proofing system utilized shall be furnished with the proofs.

These proofs must have all elements in press configuration and must indicate margins. Proofs will be used for color match on press and must show dot structure. Inkjet, photographic, and overlay proofs are not acceptable. The proofs must contain color control bars for each color of ink on the sheet. Control bars must be placed parallel to the press's ink rollers. The control bars (such as Brunner, GATF, GRETAG, or RIT) must show areas consisting of minimum 3/16 x 3/16" solid color patches; tint patches of 25, 50 and 75%; dot gain scale; and gray balance patches for process color (if applicable). These areas must be repeated consecutively across the sheet.

Proofs will be read at contractor's plant. Call (202) 512-1162 with 2 workdays notice.

CONTRACTOR MUST NOT PRINT PRIOR TO RECEIVING AN "OK TO PRINT".

BINDING:

Deliver folded to 3-2/3 x 8-1/2" using two parallel wraparound folds with title panel out. Score all folds.

PACKING:

Pack suitably per shipping container.

DISTRIBUTION:

Deliver folded forms and all furnished materials to: CDR, US Army Intelligence and Security Command, Attn: Public Affairs (703-428-4965), 8825 Beulah Street, Fort Belvoir, VA 22060-5246. No deliveries accepted after 3:00 pm, local time.

QUALITY ASSURANCE STANDARDS: The following standards shall apply to these specifications:

Inspection Levels (from ANSI/ASQC Z1.4):

- (a) Non-destructive Tests -- General Inspection Level 1.
- (b) Destructive Tests -- Special Inspection Level S-2.

Specified standards to correspond with each required attribute as follows:

ATTRIBUTESpecified Standard

P-7. Type Quality and UniformityOK Press Sheets

P-10. Process Color MatchOK Press Sheets

Special Instructions: In the event that inspection of press sheets is waived by the Government, the following listed alternate standards (in order of precedence) shall become the Specified Standards:

P-7. OK proofs/Furnished electronic media

P-10. OK proofs/Furnished electronic media